



Unit Specifications:

- Compressor: (4) Scroll, Copeland or Equivalent
- Condensers: (4) Vented Double Wall Brazed Plate
- Evaporators: (4) Single Wall Brazed Plate
- Potable Water Pump: (4) 1 HP (125 Max PSI, Standard)
- Source Water Pump: Provided by Others
- Control: Electromechanical Microprocessor (PLC)
- Frame: 304 SST (Standard)
- Approximate Ship Weight: 5300 lbs (EST)
- Refrigerant: R134a

- Available Options:
- Low Source Evaporator
  - High Source Kit
  - Insulated Cabinet
  - NEMA 1 Electrical Enclosure or Better
  - Spring Isolation Kit

- Optional Cabinet Material
- Mill Finish Aluminum
  - Galvanized Steel
  - 304 Stainless Steel
  - 316 Stainless Steel

Note: Shown Without Cabinet Option For Clarity  
 Allow 3" In All Frame Dimensions For Cabinet  
 Cabinet Will Increase Ship Weight

PROPRIETARY AND CONFIDENTIAL: SUBJECT TO CHANGE WITHOUT NOTICE  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF COLMAC INDUSTRIES. ANY  
 REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF COLMAC INDUSTRIES IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/16 ANGULAR: MACH ±1° BEND ±1 TWO PLACE DECIMAL ±0.03 THREE PLACE DECIMAL ±0.031		COLMAC INDUSTRIES 401 N. Lincoln, Colville, Washington 99114 (509)684-4505	
DRAWN BY: KLR ENGINEER: -		DATE: 10/22/2014	
REV. No. SHT. No.		REV STATUS OF SHEET	
SOLIDWORKS		AUTOCAD	
DO NOT SCALE DRAWING		SCALE: 1:4	
TITLE: GENERAL SUBMITTAL HPW60M		DWG. NO. B 1010060-0003	
UNIT WT.		*SW-Mass@Port#_SLDPR#HEET 1 OF 1	

REV. No.	REV STATUS OF SHEET
SHT. No.	