






Unit Specifications:

- Compressor: (1) Scroll, Copeland or Equivalent
- Condensers: (1) Copper Brazed with 316L plates
- Evaporators: (1) Aluminum Micro Channel (Electrocoating Optional)
- Potable Water Pump: (1) 1/2 HP SST Volute, Standard, 150 PSI Max Working Pressure
- Design Flow Rate: 18.7 GPM (10 HP), 24 GPM (15 HP) @ 15 °F TD, 100 F Air / 50% RH
- Max External Head @ Design: 24.5 ft (10 HP), 14.8 ft (15 HP)
- Source Air Fan: 1.34 HP Axial ECM, 1550 RPM
- Minimum Required Airflow: 4,700 CFM, 0.0" H2O Available
- Control: Microprocessor (PLC)
- Frame: 304 SST with Cabinet (316 SST Cabinet Optional)
- Refrigerant Type: 134a, 450 PSI Max Working Pressure
- Refrigerant Charge: 11.5 lbs (10 HP), 11 lbs (15 HP)
- Dry Weight: 885 lbs (10 HP), 895 lbs (15 HP)
- Crated Weight: 1155 lbs (10 HP), 1165 lbs (15 HP)
- Crated Dimensions: 51" x 44" x 83" (L x W x H)
- Average Sound Pressure @ 1M: 78 dB(A)


\*VALUES ARE APPROXIMATE AND FOR REFERENCE ONLY



MINIMUM DISTANCE TO OBSTRUCTION FROM EVAPORATOR INLET; RECOMMENDED 36" CLEARANCE FOR BEST PERFORMANCE



RECOMMENDED SERVICE CLEARANCE FOR SINGLE UNIT



PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF COLMAC INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF COLMAC INDUSTRIES IS PROHIBITED.

REV. No.	REV STATUS
SHT. No.	OF SHEET





UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/16 ANGULAR: MACH ±1° BEND ±1° TWO PLACE DECIMAL ±0.03 THREE PLACE DECIMAL ±0.031		CONTRACT NO.	COLMAC INDUSTRIES 401 N. Lincoln, Colville, Washington 99114 (509)684-4505	
DRAWN BY KLR		DATE	TITLE: CXA 10-15 SUBMITTAL DRAWING WITH AXIAL FAN	
ENGINEER		DATE	SIZE B	DWG. NO. 1010CXA-1015
NEXT ASSY		USED ON	REV	
APPLICATIONS		DO NOT SCALE DRAWING	SCALE: 1:24	UNIT WT.
			SHEET 1 OF 3	

12/9/2021 1010CXA-1015


Unit Specifications:

- Compressor: (1) Scroll, Copeland or Equivalent
- Condensers: (1) Copper Brazed with 316L plates
- Evaporators: (1) Aluminum Micro Channel (Electrocoating Optional)
- Potable Water Pump: (1) 1/2 HP SST Volute, Standard, 150 PSI Max Working Pressure
- Design Flow Rate: 18.7 GPM (10 HP), 24 GPM (15 HP) @ 15 °F TD, 100 F Air / 50% RH
- Max External Head @ Design: 24.5 ft (10 HP), 14.8 ft (15 HP)
- Source Air Fan: 4.8 HP Backwards Curved ECM, 1550 RPM
- Minimum Required Airflow: 5,000 CFM, 2.7" H2O Available
- Control: Microprocessor (PLC)
- Frame: 304 SST with Cabinet (316 SST Cabinet Optional)
- Refrigerant Type: 134a, 450 PSI Max Working Pressure
- Refrigerant Charge: 11.5 lbs (10 HP), 11 lbs (15 HP)
- Dry Weight: 980 lbs (10 HP), 990 lbs (15 HP)
- Crated Weight: 1350 lbs (10 HP), 1370 lbs (15 HP)
- Crated Dimensions: 51" x 44" x 96" (L x W x H)
- Average Sound Pressure @ 1M: 85 dB(A)


\*VALUES ARE APPROXIMATE AND FOR REFERENCE ONLY



MINIMUM DISTANCE TO OBSTRUCTION FROM EVAPORATOR INLET;  
RECOMMENDED 36" CLEARANCE FOR BEST PERFORMANCE



RECOMMENDED SERVICE CLEARANCE FOR SINGLE UNIT



PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF COLMAC INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF COLMAC INDUSTRIES IS PROHIBITED.

REV. No.	REV STATUS
SHT. No.	OF SHEET

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/16 ANGULAR: MACH ±1° BEND ±1° TWO PLACE DECIMAL ±0.03 THREE PLACE DECIMAL ±0.031		CONTRACT NO.	COLMAC INDUSTRIES 401 N. Lincoln, Colville, Washington 99114 (509)684-4505	
DRAWN BY KLR		DATE	TITLE: CXA 10-15 SUBMITTAL DRAWING WITH CENTRIFUGAL FAN	
ENGINEER		DATE	SIZE	DWG. NO.
NEXT ASSY		USED ON	REV	
APPLICATIONS		DO NOT SCALE DRAWING	B 1010CXA-1015	
		SCALE: 1:24	UNIT WT.	SHEET 2 OF 3

8 7 6 5 4 3 2 1

F

E

D

C

B

A

F



E

D

C

B

A



NOTE: PLENUM CAN BE ROTATED IN 90° INCREMENTS  
TO EXHAUST AIR IN ANY HORIZONTAL DIRECTION

EXHAUST GRILLE TO BE REMOVED BEFORE CONNECTING DUCTING

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF COLMAC INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF COLMAC INDUSTRIES IS PROHIBITED.

REV. No.	REV STATUS OF SHEET
SHT. No.	

**UNLESS OTHERWISE SPECIFIED:**  
DIMENSIONS ARE IN INCHES  
TOLERANCES:  
FRACTIONAL: ±1/16  
ANGULAR: MACH ±1° BEND ±1°  
TWO PLACE DECIMAL ±0.03  
THREE PLACE DECIMAL ±0.031

CONTRACT NO.	
DRAWN BY	DATE
ENGINEER	DATE
SOLIDWORKS	AUTOCAD
<b>DO NOT SCALE DRAWING</b>	




COLMAC INDUSTRIES 401 N. Lincoln, Colville, Washington 99114 (509)684-4505		
TITLE: <b>ASSY, CXA PLENUM SHROUD "C" FRAME</b>		
SIZE	DWG. NO.	REV
<b>B</b>	<b>1010CXA-1015</b>	
SCALE: 1:12	UNIT WT.	SHEET 3 OF 3

8 7 6 5 4 3 2 1


Unit Specifications:

- Compressor: (1) Scroll, Copeland or Equivalent
- Condensers: (1) Copper Brazed with 316L plates
- Evaporators: (1) Aluminum Micro Channel (Electrocoating Optional)
- Potable Water Pump: (1) 1/2 HP SST Volute, Standard, 150 PSI Max Working Pressure
- Design Flow Rate: 18.7 GPM (10 HP), 24 GPM (15 HP) @ 15 °F TD, 100 F Air / 50% RH
- Max External Head @ Design: 24.5 ft (10 HP), 14.8 ft (15 HP)
- Source Air Fan: 1.34 HP Axial ECM, 1550 RPM
- Minimum Required Airflow: 4,700 CFM, 0.0" H2O Available
- Control: Microprocessor (PLC)
- Frame: 304 SST with Cabinet (316 SST Cabinet Optional)
- Refrigerant Type: 134a, 450 PSI Max Working Pressure
- Refrigerant Charge: 11.5 lbs (10 HP), 11 lbs (15 HP)
- Dry Weight: 885 lbs (10 HP), 895 lbs (15 HP)
- Crated Weight: 1155 lbs (10 HP), 1165 lbs (15 HP)
- Crated Dimensions: 51" x 44" x 83" (L x W x H)
- Average Sound Pressure @ 1M: 76 dB(A)

\*VALUES ARE APPROXIMATE AND FOR REFERENCE ONLY




MINIMUM DISTANCE TO OBSTRUCTION FROM EVAPORATOR INLET; RECOMMENDED 36" CLEARANCE FOR BEST PERFORMANCE



RECOMMENDED SERVICE CLEARANCE FOR SINGLE UNIT

MINIMUM DISTANCE TO OBSTRUCTION FROM AXIAL OUTLET IS 30". LESS THAN THIS MAY REDUCE PERFORMANCE OR INCREASE NOISE LEVELS



PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF COLMAC INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF COLMAC INDUSTRIES IS PROHIBITED.




REV. No.	REV STATUS
SHT. No.	OF SHEET

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/16 ANGULAR: MACH ±1° BEND ±1° TWO PLACE DECIMAL ±0.03 THREE PLACE DECIMAL ±0.031		CONTRACT NO.	COLMAC INDUSTRIES 401 N. Lincoln, Colville, Washington 99114 (509)684-4505	
DRAWN BY KLR		DATE	TITLE: CXA 10-15 SUBMITTAL DRAWING WITH AXIAL FAN	
ENGINEER		DATE	SIZE	DWG. NO.
NEXT ASSY		USED ON	B 1010CXA-0015	
APPLICATIONS		SOLIDWORKS	AUTOCAD	REV
DO NOT SCALE DRAWING		SCALE: 1:24	UNIT WT.	SHEET 1 OF 3


Unit Specifications:

- Compressor: (1) Scroll, Copeland or Equivalent
- Condensers: (1) Copper Brazed with 316L plates
- Evaporators: (1) Aluminum Micro Channel (Electrocoating Optional)
- Potable Water Pump: (1) 1/2 HP SST Volute, Standard, 150 PSI Max Working Pressure
- Design Flow Rate: 18.7 GPM (10 HP), 24 GPM (15 HP) @ 15 °F TD, 100 F Air / 50% RH
- Max External Head @ Design: 24.5 ft (10 HP), 14.8 ft (15 HP)
- Source Air Fan: 4.8 HP Backwards Curved ECM, 1550 RPM
- Minimum Required Airflow: 5,000 CFM, 2.7" H2O Available
- Control: Microprocessor (PLC)
- Frame: 304 SST with Cabinet (316 SST Cabinet Optional)
- Refrigerant Type: 134a, 450 PSI Max Working Pressure
- Refrigerant Charge: 11.5 lbs (10 HP), 11 lbs (15 HP)
- Dry Weight: 980 lbs (10 HP), 990 lbs (15 HP)
- Crated Weight: 1350 lbs (10 HP), 1370 lbs (15 HP)
- Crated Dimensions: 51" x 44" x 96" (L x W x H)
- Average Sound Pressure @ 1M: 76 dB(A)



\*VALUES ARE APPROXIMATE AND FOR REFERENCE ONLY



MINIMUM DISTANCE TO OBSTRUCTION FROM EVAPORATOR INLET;  
RECOMMENDED 36" CLEARANCE FOR BEST PERFORMANCE



RECOMMENDED SERVICE CLEARANCE FOR SINGLE UNIT



PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF COLMAC INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF COLMAC INDUSTRIES IS PROHIBITED.

REV. No.	REV STATUS
SHT. No.	OF SHEET

<b>UNLESS OTHERWISE SPECIFIED:</b> DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/16 ANGULAR: MACH ±1° BEND ±1° TWO PLACE DECIMAL ±0.03 THREE PLACE DECIMAL ±0.031		CONTRACT NO.  DRAWN BY: KLR DATE: _____ ENGINEER DATE: _____ SOLIDWORKS AUTOCAD	COLMAC INDUSTRIES 401 N. Lincoln, Colville, Washington 99114 (509)684-4505 TITLE: <b>CXA 10-15 SUBMITTAL DRAWING          WITH CENTRIFUGAL FAN</b>
NEXT ASSY USED ON APPLICATIONS	DO NOT SCALE DRAWING	SIZE DWG. NO. <b>B 1010CXA-0015</b>	REV SCALE: 1:24 UNIT WT. SHEET 2 OF 3

8 7 6 5 4 3 2 1

F

E

D

C

B

A

F



E

D

C

B

A



NOTE: PLENUM CAN BE ROTATED IN 90° INCREMENTS TO EXHAUST AIR IN ANY HORIZONTAL DIRECTION

EXHAUST GRILLE TO BE REMOVED BEFORE CONNECTING DUCTING

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF COLMAC INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF COLMAC INDUSTRIES IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN INCHES  
TOLERANCES:  
FRACTIONAL: ±1/16  
ANGULAR: MACH ±1° BEND ±1°  
TWO PLACE DECIMAL ±0.03  
THREE PLACE DECIMAL ±0.031

CONTRACT NO.	
DRAWN BY	DATE
ENGINEER	DATE
SOLIDWORKS	AUTOCAD
DO NOT SCALE DRAWING	

COLMAC INDUSTRIES 401 N. Lincoln, Colville, Washington 99114 (509)684-4505		
TITLE: ASSY, CXA PLENUM SHROUD "C" FRAME		
SIZE	DWG. NO.	REV
B	1010CXA-0015	
SCALE: 1:12	UNIT WT.	SHEET 3 OF 3

REV. No.	REV STATUS OF SHEET

8 7 6 5 4 3 2 1

1010CXA-0015

9/22/2021